


## INDUSTRY-SPECIFIC APPLICATIONS FOR UV TECHNOLOGY



**APPLICATION:** Disinfection, TOC Reduction, Chlorine/Chloramines Destruction // **UV SERIES:** CSL™, Optima™, Optima HX™, SCD H™, TrojanUVLogic™

In Microelectronics, our UV systems provide a synergistic approach towards the reduction of trace organics and microbial contamination for ultrapure water.

### UV Technology

Our UV systems commonly perform four functions in producing pure water - microbial disinfection, TOC (total oxidizable carbon) reduction, ozone destruction and chlorine and chloramines reduction. They are engineered to focus the power of concentrated UV light using specially designed Aquafine Colorguard UV lamps, recognized in the industry for unsurpassed performance and reliability.

We also offer UV/H<sub>2</sub>O<sub>2</sub> advanced oxidation solutions for the reuse of spent rinse water, which provide cost savings in utilities and waste treatment/disposal.



### UV Technology for Microelectronics

We recognize the challenges faced by water professionals in the design and construction of water systems for microelectronics production. Our systems are designed to perform four functions in producing pure water - microbial disinfection, TOC reduction, ozone destruction and chlorine/chloramines reduction. Being well versed in how all components of a pure water system interrelate ensures optimum performance. Our disinfection systems address microbial contamination by destroying the DNA of microorganisms to prevent reproduction.

UV, in combination with ozone, provides a synergistic approach toward the reduction of trace organics which are among the most difficult contaminants to control in a pure water system. As critical dimensions for integrated circuits continue to decrease and transistor capacities continue to increase, contaminants in the parts per trillion ranges can produce yield-impacting defects. Organics are polar and weakly ionize in ultrapure water. This poses a considerable challenge to ion exchange resins. To prevent TOC leakage from polishing deionizers, silica and/or boron levels are typically monitored to determine when regenerations should be performed.

Our TOC reduction units complement the organic scavenger resins of the polishing loop by oxidizing trace organics into free radicals (R-OH-) and carbon dioxide, which are more readily removed by ion exchange resins and/or degasifiers. Should continuous ozone be a process requirement, our UV systems can be used to protect both product and costly microelectronic manufacturing equipment by the dissociation of ozone into dissolved oxygen. If dissolved oxygen (DO) is a concern, our engineers can provide assistance for reducing or eliminating DO as well. For these reasons, more manufacturers around the world trust Aquafine for UV systems, application assistance and support.

## UV Applications in Microelectronics

### TOC Reduction

UV systems are used for the effective reduction of organics, commonly referred to as TOC (total oxidizable carbon). Reduction of TOC is accomplished by incorporating a 185 nm UV system appropriately designed and sized as well as strategically located in conjunction with other equipment. Carbon dioxide is a typical by-product of a TOC reduction process, resulting in a drop in the resistivity of water. While most organic molecules are oxidized into carbon dioxide and water molecules, other more resistant species become weakly ionized or charged, after absorbing the UV. This is why polishing deionization (DI) beds are typically placed downstream of the TOC reduction units, so that they not only remove the charged/ionized organics, but also restore the resistivity to the water.

### Disinfection

This is the most common application of UV light in water treatment. A microelectronics water system could have several locations where UV equipment would be installed. Some typical locations would be post-carbon filter and pre-RO (reverse osmosis). When installed downstream of the carbon bed and/or directly upstream of the RO unit, a UV system can significantly reduce the microbial counts by destroying at least 99.9% of the bacteria present in the influent stream. Disinfection is also recommended for the process distribution loop and pre-storage tank.


### Ozone destruction

Ozone is commonly used in the pre-treatment area of a water system, as well as for sanitizing processes and re-circulating systems. Prior to the point-of-use, residual ozone needs to be destroyed to ensure the process water is not compromised. After considering the appropriate variables, a properly sized UV unit can be guaranteed to destroy the ozone to non-detectable limits, insuring the integrity of the process and the product. A dosage of 90 mJ/cm<sup>2</sup> is recommended for destruction of ozone residuals of 1.0ppm or less.

### Chlorine/Chloramines reduction


While the addition of chlorine and chloramines to city water may control bacteria levels, they have undesirable effects on the degradation of membrane filtration or RO. Popular methods of removal, such as carbon beds or chemical injection, have proven to be problematic. Sodium metabisulfite involves replacing one chemical with another and creates food for microorganisms, while carbon beds can be inefficient, vulnerable to channeling and provide breeding grounds for microorganisms. UV solves these problems while destroying chlorine, using a small footprint and reducing maintenance costs.

## Microelectronics Water Treatment System



Ultraviolet (UV) light is a form of light that is invisible to the human eye. It occupies the portion of the electromagnetic spectrum between X-rays and visible light. A unique characteristic of UV light is that a specific range of its wavelengths, those between 200 and 300 nanometers (billionths of a meter), are categorized as germicidal – meaning they are capable of inactivating microorganisms, such as bacteria, viruses and protozoa.

### ELECTROMAGNETIC SPECTRUM



For questions regarding your application needs, please contact your local Authorized Distributor or Aquafine for more information.

Aquafine is an ISO 9001:2008 certified company. Aquafine equipment performance is guaranteed with the use of genuine OEM replacement parts.

North America & International | 29010 Ave. Paine, Valencia, CA 91355 | P +1 661 257 4770 F +1 661 257 2489 | sales@aquafineuv.com | www.aquafineuv.com  
Europe | Ramskamp 77-85 D-25337 Elmshorn, Germany | P. +49 4121 57806 13 F. +49 4121 57806 30 | saleseu@aquafineuv.com | www.aquafineuv.com

© Aquafine Corporation 2015. All rights reserved. This document is not to be copied, electronically stored or reproduced without written permission from Aquafine Corporation. All specifications are subject to change without notice.